



CODICE	MOD.		WATT	VOLT	m ³ /H	mm. H ₂ O	Press. Pa	dB (A) 3 m.	Grado di protezione	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)
LUX 800	BORA 80-100 	80-100	7	240	130	14	137	40	IPX4	203	203	78-98	15	100
LUX 801	BORA 80-100 	80-100	7	240	130	14	137	40	IPX4	203	203	78-98	15	100
LUX 802	BORA 80-100 	80-100	7	240	130	14	137	40	IPX4	203	203	78-98	15	100
LUX 803	BORA 80-100 	80-100	7	240	130	14	137	40	IPX4	203	203	78-98	15	100
LUX 804	BORA 80-100C 	80-100	7	240	130	14	137	40	IPX4	203	203	78-98	15	100
LUX 805	BORA 80-100C  	80-100	7	240	130	14	137	40	IPX4	203	203	78-98	15	100
LUX 806	BORA 80-100C  	80-100	7	240	130	14	137	40	IPX4	203	203	78-98	15	100
LUX 807	BORA 80-100C  	80-100	7	240	130	14	137	40	IPX4	203	203	78-98	15	100
LUX 808	BORA 80-100 	80-100	7	12	130	14	137	40	-	203	203	78-98	15	100
LUX 809	BORA 80-100C  	80-100	7	12	130	14	137	40	-	203	203	78-98	15	100

 Foro di uscita in mm.
Outlet hole mm.
Trou de sortie en mm

 Apertura fissa
Fixed opening
Ouverture fixe

 Apertura e chiusura automatica
Automatic opening/closing
Ouverture et fermeture automatique

 Timer regolabile (min. 5 - max 30 minuti)
Adjustable timer (min. 5 - max 30 minutes)
Temporisateur réglable (min. 5 - max 30 minutes)

 Sensore di umidità regolabile (min. 10% - max 90%)
Adjustable humidity sensor (min. 10% - max 90%)
Capteur d'humidité réglable (min. 10% - max 90%)

 Interruttore con cordicella
Switch with pullcord
Interruteur à cordon

 12 Volt
12 Volt
12 Volt