











CODICE	MOD.		WATT	VOLT	m ³ /H	mm. H ₂ O	Press. Pa.	dB (A) 3 m.	Grado di protezione	A (mm)	B (mm)	C (mm)
LUX 450	ETESI 100		15	240	120	3	29	36	IPX4	97	97	106
LUX 451	ETESI 100 		15	240	120	3	29	36	IPX4	97	97	106
LUX 452	ETESI 100 		15	240	120	3	29	36	IPX4	97	97	106
LUX 453	ETESI 120		15	240	160	4	39	38	IPX4	118	118	108
LUX 454	ETESI 120 		15	240	160	4	39	38	IPX4	118	118	108
LUX 455	ETESI 120 		15	240	160	4	39	38	IPX4	118	118	108
LUX 456	ETESI 150		15	240	180	5	49	38	IPX4	146	146	108
LUX 457	ETESI 150 		15	240	180	5	49	38	IPX4	146	146	108
LUX 458	ETESI 150 		15	240	180	5	49	38	IPX4	146	146	108

 Foro di uscita in mm.
Outlet hole mm.
Trou de sortie en mm

 Timer regolabile (min. 5 - max 30 minuti)
Adjustable timer (min. 5 - max 30 minutes)
Temporisateur réglable (min. 5 - max 30 minutes)

 Sensore di umidità regolabile (min. 10% - max 90%)
Adjustable humidity sensor (min. 10% - max 90%)
Capteur d'humidité réglable (min. 10% - max 90%)