
































CODICE	MOD.		WATT	VOLT	m <sup>3</sup> /H	mm. H <sub>2</sub> O	Press. Pa	dB (A) 3 m.	Grado di protezione	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	
LUX 301	LEVANTE 80 		80	15	240	60	2	20	36	IPX4	163	163	78	70	34
LUX 302	LEVANTE 80 		80	15	240	60	2	20	36	IPX4	163	163	78	70	34
LUX 303	LEVANTE 80 		80	15	240	60	2	20	36	IPX4	163	163	78	70	34
LUX 304	LEVANTE 100 		100	15	240	100	4	39	36	IPX4	163	163	98	70	34
LUX 305	LEVANTE 100C 		100	15	240	100	4	39	36	IPX4	163	163	98	70	34
LUX 306	LEVANTE 100 		100	15	240	100	4	39	36	IPX4	163	163	98	70	34
LUX 317	LEVANTE 100C  		100	15	240	100	4	39	36	IPX4	163	163	98	70	34
LUX 307	LEVANTE 100 		100	15	240	100	4	39	36	IPX4	163	163	98	70	34
LUX 318	LEVANTE 100C  		100	15	240	100	4	39	36	IPX4	163	163	98	70	34
LUX 308	LEVANTE 120 		120	15	240	140	5	49	38	IPX4	163	163	118	70	34
LUX 309	LEVANTE 120C 		120	15	240	140	5	49	38	IPX4	163	163	118	70	34
LUX 310	LEVANTE 120 		120	15	240	140	5	49	38	IPX4	163	163	118	70	34
LUX 319	LEVANTE 120C  		120	15	240	140	5	49	38	IPX4	163	163	118	70	34
LUX 311	LEVANTE 120 		120	15	240	140	5	49	38	IPX4	163	163	118	70	34
LUX 320	LEVANTE 120C  		120	15	240	140	5	49	38	IPX4	163	163	118	70	34
LUX 312	LEVANTE 150 		150	15	240	160	5	49	38	IPX4	163	163	148	70	34
LUX 313	LEVANTE 150C 		150	15	240	160	5	49	38	IPX4	163	163	148	70	34
LUX 314	LEVANTE 150 		150	15	240	160	5	49	38	IPX4	163	163	148	70	34
LUX 321	LEVANTE 150C  		150	15	240	160	5	49	38	IPX4	163	163	148	70	34
LUX 315	LEVANTE 150 		150	15	240	160	5	49	38	IPX4	163	163	148	70	34
LUX 322	LEVANTE 150C  		150	15	240	160	5	49	38	IPX4	163	163	148	70	34

 Foro di uscita in mm.  
Outlet hole mm.  
Trou de sortie en mm

 Apertura e chiusura automatica  
Automatic opening/closing  
Ouverture et fermeture automatique

 Sensore di umidità regolabile (min. 10% - max 90%)  
Adjustable humidity sensor (min. 10% - max 90%)  
Capteur d'humidité réglable (min. 10% - max 90%)

 Apertura fissa  
Fixed opening  
Ouverture fixe

 Timer regolabile (min. 5 - max 30 minuti)  
Adjustable timer (min. 5 - max 30 minutes)  
Temporisateur réglable (min. 5 - max 30 minutes)